



KRAMER

WP-872xr

ウォールプレート型 4K HDR HDMI ツイストペア受信器
DGKat 2.0

| HDMI | DGKat | 4K/60 UHD (4:4:4)



WP-872xrは、4K@60(4:4:4)、HDRおよび HDCP2.2対応 DGKatウォールプレートレシーバーです
送信されたDGKat2.0信号をHDMI信号に変換します。
WP-872xrは、4K@60Hz(4:4:4)解像度で最大60mまで、
4K@30Hz(4:4:4)24bpp解像度で最大70mまでKramer製 STPケーブルで延長可能です
このウォールプレート型伝送器は、ツイストペアケーブルでPoC (Power over Copper)を介して電力を供給もしくは受電することができます

FEATURES

- 高性能レシーバー** - ツイストペアケーブルで長距離伝送を提供するレシーバー
WP-872xrは、4K信号に対して視覚的にロスのない低レベルのビデオ圧縮技術を採用しています
送信されたDGKat2.0信号をHDMI信号に変換します
- HDMI信号伝送** - HDR/HDCP 2.2, ディープカラー, x.v.Color™, リップシンク, HDMI非圧縮音声チャンネル, Dolby TrueHD, DTS-HD, 2K, 4K, および HDMI 2.0で指定された3D
- EDID パススルー** - パススルーアルゴリズムにより、HDMIソースおよびディスプレイシステムのプラグアンドプレイ操作が保証されます
- マルチチャンネルオーディオ伝送** - スタジオグレードサラウンドサウンドをサポートするための最大32チャンネルのデジタルステレオ非圧縮信号
- 費用対効果の高いメンテナンス** - 電源および接続ステータスLEDインジケーターにより、ローカルメンテナンスとトラブルシューティングが容易になります
- 簡単な設置** - 米国、EU、英国の標準的な1ギャングのインウォールボックスサイズに収まります
ウォールプレートの設置はツイストペアケーブルを介して高速で費用対効果が高く、ビデオ信号と電源(PoC)接続の両方を提供します



KRAMER

TECHNICAL SPECIFICATIONS

入力	1 DGKat RJ-45 (Female)
出力	1 HDMI (Female)
VIDEO	最大データ転送レート 18Gbps (各映像信号系統につき6Gbps) 最大解像度 3840x2160@60Hz (4:4:4) 24bpp HDR10, HDCP 2.2準拠
伝送距離	KramerUsing Shielded UNIKAT Cables Up to 60m (200ft) at 4K@60Hz (4:4:4), Up to 70m (230ft) at 4K@30Hz (4:4:4) or full HD (1080p @60Hz 36bpp)
Extension Line	Signal Compression: High compression level applied to >1080p signals Compliance: DGKat 2.0
User Interface	Indicators: Power/connection Controls: Dip-switches to define compression setup
Power	Source: 12V DC, 2A Consumption: 580mA
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RHL non-condensing
Enclosure	Size: 1-gang Type: Aluminum Cooling: Convection ventilation
Accessories	Included: Power adapter with cord, bracket set
STANDARDS COMPLIANCE	Safety: CE, UL Environmental: RoHs, WEEE
Product Dimension	US: 6.98cm x 3.10cm x 11.43cm (2.75" x 1.22" x 4.50") W, D, H
Product Weight	US: 0.1kg (0.1lbs) approx
Shipping Dimension	US: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H
Shipping Weight	US: 0.6kg (1.2lbs) approx



KRAMER

CONFIGURATIONS

WP-872XR/US(W/B) US-D-size Wall-Plate Transmitter, with White & Black Decora® Design Frame Sets

WP-872XR/EU-80/86(W) EU & UK-size Wall-Plate Transmitter, with EU & UK White Frames

